

LDACI225TNS01

EN 54-24

LDA CI225-TN is a high-performance 20W voice alarm column loudspeaker for indoor or outdoor use and it is EN 54-24 certified. It provides a broad frequency response range, low distortion and high sound pressure level for accurate and intelligible broadcast of evacuation messages and high quality sound reproduction. Its low-profile, white color design blends easily with most interiors in locations such as hotels, conference rooms, cinemas, theme parks, factories and exhibitions.



Features of the CI-225TN:

- EN 54-24 certified
- Intelligible voice and superior sound reproduction
- Robust aluminum housing
- Includes universal swivel bracket for easy angle adjustment
- Able to be switched between 100V and 70V
- Adapts to extreme environment
- IP66 compliant

Technical Specifications:

Model	LDACI225TNS01
Max power	30 W
Rated power	20 W
Power tapping	20W / 10W / 5W / 2.5W @ 100V
SPL at 20W/1W (100Hz-10kHz, 1m)	103 dB (40W/1m) / 92 dB (1W/1m)
Frequency response	300 Hz ~15 kHz
Connection	Fire-resistant cable
Dimensions (W x H x D)	165 x 150 x 344 mm
Weight	3.75 kg
Color	White (RAL9003)
Speaker size	4" x 2
Material	Aluminum