

CI-625T

The CI-625 is a high performance column speaker for professional installations.

Its stylized design allows to adapt it to all the environments in addition to IP protection. The CI-625 can be installed on wall or columns. For that reason, it has a bracket which allows to install the acoustic box in vertical or horizontal position and rotate it 180° around itself.

The 6 drivers of 2.5", contained inside of it, give to any installation a high fidelity of sound by means of the adaptable acoustic design.



CI-625T features:

- High sensitivity: 92 dB (1 W, 1 m)
- High quality audio for music or voice
- Low loss transformer for 70/100V PA lines
- Easy to install
- Metallic grille acoustically transparent

Technical specifications:

Modelo	LDACI625TS01
NOMINAL POWER	30 W RMS
FREQUENCY RESPONSE	170 Hz- 15 kHz
SENSITIVITY	92 dB +/- 3 dB (1W, 1m)
MATERIAL	Al (body) Fe (grille)
COLOUR	White, RAL 9016
CONNECTOR	N/A. 3-wire cable with feedthrough
FIXING	Wall-mount with 2 metal brackets. Adjustable angle up to 15°
TRANSFORMER (70/100 V)	30/15 W @100 V 15/7.5 W @70 V
DIMENSIONS (height x width x depth)	548 x 106 x 75 mm
WEIGHT	2.74 kg