

CS-42T

The CS-42T is a ceiling speaker with high sensitivity. The enclosure and the grille are both made of metal. It provides an easy installation with a 34 contacts barrier strip connector. Thanks to its integrated impedance transformer, it is possible to install it in 70/100 V PA lines choosing the power configuration most suited to the needs of the venue.

The installation is very quick and flexible thanks to the metal clamps, which allow to install the speaker both into metallic sheet tile and plaster ceilings.

Features CS-42T:

- High performance: 92 dB (1 W, 1 m)
- Excellent quality of music and voice playback
- Low lost transformer for 70/100 V PA lines
- Easy to install
- Metallic grille acoustically transparent



Technical specifications:

Model	LDACS42TS01
NOMINAL POWER	6 W RMS
FREQUENCY RESPONSE	100Hz- 18 kHz +/- 5dB
SENSITIVITY	92 dB +/- 3 dB (1W, 1m)
MATERIAL	Iron (body and grille)
COLOUR	White, RAL 9016
CONNECTOR	Barrier strip type
FIXING	Installation by metallic clamps for metallic sheet tile and plaster ceilings.
TRANSFORMER (70/100 V)	6 W or 3 W @100 V 3 W or 1,5 W @70 V
DIMENSIONS (diameter x depth)	200 x 65 mm
DRILL HOLE FOR MOUNTING	185 mm
WEIGHT	0,8 kg